



PM 360 FTTH OUTDOOR CABINET

2x28U PASSIVE, 350 mm DEPTH



GRL009170A (FTTH G2 SP 2x28U D350 - PM360)

GROLLEAU propose a 2x28U single skin outdoor SRO 350 mm depth. The cabinet is full **removable** and **reassemblable, without service interruption.**

Aluminium **single skin** cabinet has a door, a roof, baseboards and **removable panels from the inside**, easily replaceable.

MADE IN FRANCE



COMPLIANCE

- ▶ Climatic environment IEC 60068-2-2
- ▶ Corrosion IEC 60068-2-11
- ▶ Earthing
- ▶ IP protection NF EN 60529 / IP55
- ▶ Shock resistance EN 62262 / IK10
- ▶ Strength NF EN 61587-1 / 500N
- ▶ Vibration NF EN 61300-2-1

REFERENCED CABINET BY THE FRENCH HISTORIC OPERATOR

MECHANICAL CHARACTERISTICS

Type	PM 360 FTTH PASSIVE Single skin conception 2x28U
Overall dimensions	W1600 x D350 x H1625 mm
Weight without equipments	100 kg
Cabinet	SRO single skin 2x28U, 350 mm depth
Height of pedestal	200 mm
Operating depth	40 mm between front face, equipments and door 290 mm for integration of equipments
Opening door	90 nd 110°
	2 columns 19" 28U separated by a optical cable's resorber

FINITION & PROTECTION

Standard protection	IP 55 IK 10
Locking	points by european half cylindrical lock
Painting	10 standard textured RAL colors
Floor fixation	8 points accessibles from the inside of cabinet M10 screws & washers delivered with cabinet
Hinges & bolts	Strainless steel
Compartment support OF	1 adjustable rear frame 19", resorber side
Briefcases	2 briefcases A4
Ventilation	Natural ventilation by holes in upper and lower part



PM 360 FTTH OUTDOOR CABINET

2x28U PASSIVE, 350 mm DEPTH

INTEGRATION CHARACTERISTICS

Input cables	12 inputs at the bottom of column 19" (diameter 5 to 17 mm) 2 manholes for passage of cables
Optical cable	L : 3,5 m - Ø : 1,6 mm
	Deck reception of BAE tiedowns at the bottom of each column
Guide tubes pins	In the back of column
Central resorber	With 7 vertical drums & 4 offset drums for the brewing of opticals cables
Rings, Guide cables	On 19" amount resorber side
Pigtails collection	Specific progression
Plan of brewing	On the door
Installation	Earthing of cabinet by dowel through, accessible in the pedestal Equipotentiality realised on whole cabinet



FTTH G2 SP 2x28U D350 - PM360

OPTIONS

Template for fixation	In a concrete apron with sheath reservation in correspondence with entries of cables
Embase	Precasted in GRC (Glass - Reinforced fiber - Cement)
Colors	Specific RAL colors
Protection	Anti-display realised by bumped conessor on all cabinet sides



FTTH G2 SP 2x28U D350 E - PM360

REFERENCES

FTTH G2 SP 2x28U D350 - PM360 (standard)	GRL009170A
FTTH G2 SP 2x28U D350 E - PM360 (pyramidal stamps - anti-display)	GRL009171A
FTTH G2 SP 2x28U D350 B - PM360 (round stamps - anti-display)	GRL010846A
Template	GRL009182A
Embase	GRL010368A

Standard



Pyramidal stamps



Round stamps

